

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 May 2001 (17.05.2001)

PCT

(10) International Publication Number
WO 01/34083 A1

(51) International Patent Classification⁷: A61F 13/494

(21) International Application Number: PCT/JP00/07754

(22) International Filing Date:
2 November 2000 (02.11.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11/320340 10 November 1999 (10.11.1999) JP

(71) Applicant (for all designated States except US): KAO
CORPORATION [JP/JP]; 14-10, Nihonbashi Kayaba-cho
1-chome, Chuo-ku, Tokyo 103-8210 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KASAI, Takao
[JP/JP]; c/o Kao Corporation, Research Laboratories,
2606, Akabane, Ichikai-machi, Haga-gun, Tochigi

321-3426 (JP). MAEDA, Kazuyuki [JP/JP]; c/o Kao
Corporation, Research Laboratories, 2606, Akabane,
Ichikai-machi, Haga-gun, Tochigi 321-3426 (JP). ITOH,
Taketo [JP/JP]; c/o Kao Corporation, Research Labora-
tories, 2606, Akabane, Ichikai-machi, Haga-gun, Tochigi
321-3426 (JP).

(74) Agents: HATORI, Osamu et al.; Akasaka HKN Building,
6F, 8-6, Akasaka 1-chome, Minato-ku, Tokyo 107-0052
(JP).

(81) Designated States (national): CN, KR, US.


(84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ABSORBENT ARTICLE



(57) Abstract: An absorbent article comprises a liquid-permeable topsheet, a liquid-impermeable backsheet and a liquid-retentive absorbent core interposed between the topsheet and the backsheet. The absorbent article is substantially vertically elongated and has an upstanding gather. The topsheet has a liquid shut-off region in a line shape and adapted to prohibit migration of a liquid in the topsheet. The liquid shut-off region is formed at a region outside a peripheral edge portion but other than a joined section between the topsheet and a sheet material for forming the upstanding gather.

WO 01/34083 A1

DESCRIPTION

ABSORBENT ARTICLE

TECHNICAL FIELD

5 The present invention relates to an absorbent article such as a disposable diaper which is excellent in anti-leak properties.

BACKGROUND ART

10 In a conventional disposable diaper, it sometimes occurs that a discharged body liquid migrates through the interior of a topsheet under the effect of capillary action and reaches a peripheral edge portion with a result of leakage therefrom. As a technique for preventing the leak of a liquid from the opposite side edge portions in the longitudinal direction of the diaper, Japanese Patent Application Laid-open No. 63-182401 proposes a diaper in which a sheet material for forming an upstanding gather and a topsheet are joined together at an upper part of an absorbent core and the leak of a body liquid from opposite side edge portions of the diaper is restrained by utilizing the joined section (or junction).

15 However, since the topsheet of this diaper is designed such that its end portion does not reach an end portion of the product and joining means for joining the upstanding gather serves as leak restraining means, the processing conditions for joining a plurality of sheets are limited. Moreover, in the case where an adhesive agent is used as means for joining the upstanding gather and the topsheet together, in the case where the topsheet is a bulky nonwoven fabric, a large amount of adhesive agent must be used for the adhesion thereof and for the restraint of leak thereof, thus resulting in problems of impairment of flexibility and increase in manufacturing cost. Moreover, in the case where a continuous production is to be performed, the topsheet must be arranged intermittently in a direction of the flow of a raw fabric, thus resulting in serious deterioration in productivity. In addition, the anti-leak effect is not sufficient, as well.

DISCLOSURE OF THE INVENTION

It is, therefore, an object of the present invention to provide an absorbent article which is good in workability (or processibility), which can exhibit a satisfactory anti-leak effect even when a bulky topsheet is employed, which is good in productivity and which is low in manufacturing cost.

- 5 The present invention has achieved the above object by providing an absorbent article including a liquid-permeable topsheet, a liquid-impermeable backsheet and a liquid-retentive absorbent core interposed between the topsheet and the backsheet, the absorbent article being substantially vertically elongated and having an upstanding gather,
- 10 wherein the topsheet has a liquid shut-off region in a linear shape which prevents liquid migration within the topsheet, and the liquid shut-off region is located at an area outside the periphery of the absorbent core and is formed independent of a joined section between the topsheet and a sheet material for forming the upstanding gather..

BRIEF DESCRIPTION OF THE DRAWINGS

- 15 FIG. 1 is a plan view, when viewed from a topsheet side, showing one state of a disposable diaper according to one embodiment of the present invention, in which an elastic member is in a stretched position;
- FIG. 2 is a sectional view taken on line X-X of FIG. 1;
- FIG. 3 is a sectional view taken on line Y-Y of FIG. 1;
- 20 FIG. 4 is an explanatory view for explaining the location where a liquid shut-off region is formed;
- FIG. 5(a) is an illustration showing one example of a method for forming a liquid shut-off region, and FIG. 5(b) is an illustration showing another example thereof;
- FIG. 6 is a sectional view (corresponding to FIG. 3) showing a disposable diaper
- 25 according to another embodiment of the present invention; and
- FIG. 7 is a sectional view (corresponding to FIG. 3) showing a disposable diaper according to a further embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

- 30 An preferred embodiment of the present invention will be described hereinafter. A disposable diaper 1 as an absorbent article in this embodiment is a so-called flat-type

disposable diaper including a liquid-permeable topsheet 2, a liquid-impermeable
backsheet 3 and a liquid-retentive absorbent core 4 interposed between the topsheet 2
and the backsheet 3, the disposable diaper 1 being substantially vertically elongated and
having a pair of left and right fastening tapes 5, 5 at opposite side edge portions of its
back side B.

The topsheet 2 and the backsheet 3 each have a vertically elongated configuration and
joined together at a peripheral edge portion extending outward beyond the absorbent
core 4. The absorbent core 4 has a vertically elongated configuration and it is fixedly
sandwiched between the topsheet 2 and the backsheet 3. Opposite end edges 2a, 2b of
the topsheet 2 in the longitudinal direction of the diaper 1 and opposite left and right
side edges 2c, 2c of the topsheet 2 in the longitudinal direction of the diaper 1 are
extended to opposite end edges 1a, 1b and opposite side edges 1c, 1c of the diaper 1,
respectively. On opposite side regions in the longitudinal direction of the diaper 1,
sheet materials 61, 61 for forming upstanding gathers are arranged to form a pair of left
and right upstanding gathers 6, 6.

As shown in FIG. 3, the sheet material 61 for forming the upstanding gather is disposed
inward of the diaper from each side edge in the longitudinal direction of the diaper.
An elastic member 62 is fixed, in its stretched state, to a free end portion 60 on the
widthwise center side of the disposable diaper 1 along an end edge of the free end
portion 60. The sheet material 61 is secured to an upper part of each side portion 4c of
the absorbent core 4 by thermal-fusing or adhesive agent. By the joining of the sheet
material 61 to the upper part of each side portion, a basal end 63 of the upstanding
gather 6 is formed. Each sheet material 61 extends outward beyond each side edge
portion 4c in the longitudinal direction of the absorbent core 4 so that a side edge 61c,
which is located on the other side of the side edge portion forming the free end portion
60, is located at the side edge 1c of the diaper 1. The sheet material 61 is in intimate
contact with the topsheet 2 at its extended section. A plurality of elastic members 64,
64, as shown in FIG. 3, are fixedly arranged, in their stretched states and in parallel with
the elastic member 62, between the elastic member 62 and the basal end 63 in each
sheet 61.

Waist portion elastic members 81, 81 for forming waist gathers are disposed at opposite end portions in the longitudinal direction of the disposable diaper 1 but the upstanding gathers are not formed thereon.

5 The topsheet 2 of the disposable diaper 1 has a liquid shut-off region 21 in a linear shape which prevents liquid migration within the topsheet 2. The expression "in a linear shape" used herein refers to a line effective for restraining the penetration of a body liquid but it does not necessarily mean that the seal lines, etc. are continuously formed without interruption. For example, if intermittent seal lines placed one upon another and arranged in array can prohibit the migration of a body liquid within the
10 topsheet 2, this arrangement can be said as "in a linear shape". The concept of the expression "in a linear shape" includes not only a straight-line shape but also a curved-line shape and a bent-line shape. The width of the line is preferably about 0.5 to 15 mm. The liquid shut-off regions 21 are located on the opposite longitudinal end portions and the opposite side portions of the diaper 1. The liquid shut-off regions
15 21A, 21B located on the longitudinal end portions, respectively, are in a linear shape over the widthwise direction of the diaper 1, whereas the liquid shut-off regions 21C, 21C located on the side portions, respectively, are in a linear shape over the longitudinal direction of the diaper 1.

20 More specifically, the liquid shut-off regions 21A, 21B of the opposite end portions in the longitudinal direction of the diaper 1 are formed over a region between the opposite side edges of the absorbent core 4 along the opposite end edges of the absorbent core 4, whereas the opposite left and right liquid shut-off regions 21C, 21C are formed over a region between the opposite end edges of the absorbent core 4 along the opposite left and right side edges of the absorbent core 4. In the case where the liquid shut-off
25 regions 21A, 21B are formed on the regions outside the end edges in the longitudinal direction of the absorbent core 4 (the same direction as the longitudinal direction of the absorbent article), the lengths L1 (only one is shown) of the liquid shut-off regions 21A, 21B are preferably larger than 100% of the length L2 (only one is shown) of the opposite end edges of the absorbent core 4 and terminated in the product. In the case
30 where the liquid shut-off regions 21C, 21C are formed on the regions outside the side edges in the longitudinal direction of the absorbent core 4, the lengths L3 (only one is

shown) of the liquid shut-off regions 21C, 21C are preferably larger than 100 % of the length L4 (only one is shown) of the opposite side edges of the absorbent core 4 and terminated in the regions inside the opposite ends 1a, 1b in the longitudinal direction of the product.

5 In this embodiment, the liquid shut-off regions 21A, 21B and the liquid shut-off regions 21C, 21C are mutually connected together at areas in the vicinity of the four corner portions of the absorbent core 4. The absorbent core 4 is surrounded with the liquid shut-off region 21 at area outside its peripheral edge portion over the entire periphery. In this embodiment, each liquid shut-off region 21 is generally a straight line.

10 Each liquid shut-off region 21 is formed at a region outside the peripheral edge portion of the absorbent core 4. That is to say, the liquid shut-off regions 21A, 21B are formed at regions outside the opposite end edges in the longitudinal direction of the absorbent core 4, whereas the liquid shut-off regions 21C, 21C are formed at regions outside the opposite left and right side edges in the longitudinal direction of the absorbent core 4.
15 Owing to this feature, even if a body liquid should migrate through the interior of the topsheet, the body liquid would not leak from the peripheral edge portion of the diaper because it would collide against any or some of the liquid shut-off regions so that further movement of the body liquid is prohibited. That is to say, the leak of a body liquid from the waist portion is prevented by the liquid shut-off regions 21A, 21B and
20 the leak from the leg areas is likewise prevented by the liquid shut-off regions 21C, 21C.

In the disposable diaper 1 of this embodiment, since the liquid shut-off regions 21A, 21B are formed on the opposite end portions in the longitudinal direction of the diaper over the widthwise direction of the diaper, a similar anti-leak effect to one having a
25 waist upstanding gather can be obtained nevertheless it has no waist upstanding gather.

As shown in FIGS. 2 and 3, the respective liquid shut-off regions 21 are formed independent of a joined section S between the topsheet 2 and the sheet material 61 for forming the upstanding gather. That is to say, the respective liquid shut-off regions 21 are formed at other regions than a joined section S between the topsheet 2 and the sheet
30 material 61. The liquid shut-off regions 21 are not formed at the time the sheet

material 6 for forming the upstanding gather is joined to the topsheet 2.

The expression "joined section" between the topsheet and the sheet material for forming the upstanding gather used herein refers to an adhesive layer and a hot-melt layer which are formed between the topsheet and the sheet material for forming the upstanding gather when the topsheet and the sheet material are joined together. As a material for forming the adhesive layer, there can be listed an adhesive agent such as a hot-melt. The hot-melt layer is formed on an interface between the topsheet and the sheet material for forming the upstanding gather by applying a heat-seal, an ultrasonic-seal or the like to the sheet material and the topsheet to melt a part of the sheet material and/or the topsheet. The expression "the liquid shut-off region is formed independent of a joined section" means not only a case that the liquid shut-off region and the "joined section" as defined above are not overlapped with each other when the diaper is viewed in the sectional direction (indicated by an arrow P in FIG. 4), but also a case that the liquid shut-off region and the "joined section" are not overlapped with each other when the diaper is viewed in the horizontal direction (indicated by an arrow Q in FIG. 4). The liquid shut-off region in the present invention includes, for example, those in which the liquid shut-off region as indicated by D and E of FIG. 4 is not overlapped with the joined section S when the absorbent article is viewed not only in a plan view but also in the sectional direction. It also includes, for example, those in which the liquid shut-off region as indicated by F of FIG. 4 is overlapped with the joined section S when the absorbent article is viewed in a plan view but the liquid shut-off region is not overlapped with the joined section S when the absorbent article is viewed in a sectional direction (see FIG. 4) in the widthwise direction thereof. Embodiments for forming the liquid shut-off region independent of the joined section include (1) forming the joined section by using an adhesive while forming the liquid shut-off region by the other means than that of the joined section such as a heat-seal and an ultrasonic-seal, and (2) forming the both by the same means but making the both differ in the position to be formed in the extending direction of the sheet material for forming the upstanding gather. Since the liquid shut-off region is for preventing a body liquid from leaking out due to the liquid migration within the topsheet, it is preferably formed over the entire width dimension of the topsheet. FIG. 4 shows a joined section (adhesive layer) S formed by joining the sheet material 61 for forming the upstanding gather to the

topsheet through an adhesive agent.

By forming the liquid shut-off region 21 to be independent of the joined section between the sheet material 61 and the topsheet 2, the working (or processing) conditions required at the time of joining the sheet material 61 for forming an upstanding gather are not limited, the sheet material 61 can be joined to the topsheet 2 by an appropriate method even in the case where a bulky nonwoven fabric is used for the topsheet 2.

It is preferable that the liquid shut-off region 21 in the present invention be formed independent of a joined section between the topsheet 2 and other sheets (sheet material 61, backsheet 3, etc.).

Accordingly, the diaper 1 can be manufactured economically. The topsheet 2 in this embodiment is not thermally bonded to other sheet materials (the sheet material 61 and the backsheet 3) at the respective liquid shut-off regions 21. The bulky topsheet is a sheet manufactured, for example, by an air-laid, air-through system. It has a basis weight of 20 g/m² or more, preferably 25 g/m² or more and a thickness of 0.3 mm or more, preferably 0.6 mm or more.

According to this diaper 1, since the opposite end edges 2a, 2b of the topsheet 2 extends to the opposite end edges 1a, 1b of the diaper 1, it is not necessary to intermittently arrange the topsheets 2 in the case where diapers are continuously manufactured with the longitudinal direction of the diaper serving as a flow direction. Moreover, since the opposite side edges 2c, 2c of the topsheet 2 are extended to the opposite side edges 1c, 1c of the diaper 1, it is not necessary to intermittently arrange the topsheets 2 even in the case where the widthwise direction of the diaper serves as a flow direction.

The liquid shut-off region 21 in this embodiment is formed by heat seal.

That is to say, the topsheet 2 is a sheet of nonwoven fabric which comprises a thermally fusible material, more particularly is composed of a thermally fusible synthetic fiber. Each liquid shut-off region 21 is formed by pressing a heat-seal material such as a heat roll against the sheet so as to melt a part of the sheet. In the case where the liquid shut-off region is formed by heat seal, the seal width is preferably 0.2 to 15 mm and particularly preferably 0.5 to 5 mm from the view point of strength, liquid shut-off property and high productivity.

Moreover, in this disposable diaper 1, as shown in FIG. 3, the liquid-permeable topsheet 2, which covers the skin contacting surface (that surface which is faced with the wearer's skin side) of the absorbent core 4, extends outward (outward in the widthwise direction) beyond the basal ends 63 of the upstanding gathers 6 form on the opposite side portions in the longitudinal direction of the diaper, and at least a part of the extended section (the same direction as the widthwise direction of the diaper) of the topsheet 2a extending outward beyond the basal ends is joined to the backsheet through an adhesive agent, not shown. The two liquid shut-off regions 21C are each formed on the extended topsheet 2a which extend outward beyond the basal ends 63 of the upstanding gathers.

In this diaper 1, since the extended section 2a of the liquid-permeable topsheet 2 is present at the back side of that portion of the sheet material 61 for forming an upstanding gather which is located outside the basal end 63 in the widthwise direction, a good moisture absorbing property can be obtained at opposite side portions of the diaper even in the case where a hydrophobic sheet material is used as the sheet material 61 for forming an upstanding gather, thus enabling to prevent the generation of heat rash.

Moreover, in this diaper 1, the sealing between the sheet material 61 and the backsheet 3 at opposite side portions of the diaper is achieved by the adhesive agent for joining the sheet material 61 for forming an upstanding gather and the topsheet 2 together, the liquid shut-off regions 21C formed on the topsheet 2 and the adhesive agent for joining the topsheet 2 and the backsheet 3 together. Owing to this feature, the feeling at the opposite side portions of the diaper is not degraded and the backsheet 3 is not damaged, either.

This diaper 1 can easily be manufactured by preliminarily forming the respective liquid shut-off regions 21 on the topsheet 2 and then arranging the topsheet 2 with the liquid shut-off regions 21 formed thereon at a predetermined location of the diaper 1. This manufacturing method is one embodiment of a method for manufacturing an absorbent article of the present invention. As a method for forming the liquid shut-off regions, the liquid shut-off regions 21A to 21C may all be formed simultaneously using a single heat-seal member or after the liquid shut-off regions 21A, 21B are formed by a single

heat-seal member, the liquid shut-off members 21C, 21C may be formed by another heat-seal member. This order may be reversed. Moreover, the liquid shut-off region 21A and the liquid shut-off region 21B, and both the liquid shut-off regions 21C, 21C may be formed using different heat seal members, respectively. In the case where the liquid shut-off regions are formed by heat-seal, the topsheet may be sandwiched between and pressed by the heat-seal members from the opposite surfaces as shown in FIG. 5(a). It is also accepted that the topsheet 2 is folded back and the folded-back portion 22 is sandwiched between and pressed by the heat seal members from the opposite sides as shown in FIG. 5(b).

The diaper 1 of this embodiment can be manufactured by arranging the topsheet 2 with the liquid shut-off regions 21A, 21B, 21C, 21C formed thereon at a predetermined location in the diaper 1 so that the liquid shut-off regions 21A, 21B, 21C, 21C are arranged at the locations as shown in FIGS. 1 to 3, respectively. By preliminarily forming the liquid shut-off regions 21 on the topsheet 2 and then arranging the topsheet with the liquid shut-off regions 21 formed thereon at a predetermined location as just mentioned, a wide variety of joining methods can selectively be used when the sheet material 61 for forming an upstanding gather is joined to the topsheet 2. Hence, the best joining method can be selected taking into consideration the economical efficiency, etc. By this, the productivity of a diaper is enhanced and an economically efficient manufacture can be obtained. It should be noted that those points, which are not particularly described in this embodiment, are the same as in the conventional method for manufacturing a diaper.

It is necessary that the liquid shut-off regions are formed in such a manner as to be able to prohibit the migration of a body liquid through the interior of the topsheet. In the case where a nonwoven fabric is used for the topsheet and the liquid shut-off regions are formed by heat-sealing the nonwoven fabric, it is preferred that they are processed at a temperature of the melt point (m. p.) of the component fiber of the nonwoven fabric or higher and it is more preferable that they are processed at a temperature of the melt point plus 20 °C or higher. It is also effective to use a fiber of a core-sheath structure as the component fiber in order to maintain the strength of the nonwoven fabric. In that case, it is preferable that a resin having a high melt point is used as the core, a resin

having a low melt point is used as the sheath and they are processed at temperatures equal to or higher than the melt point of the sheath component but lower than the melt point of the core component. For example, in the case where the core fiber is PET and the sheath component is PE, sealing is performed at temperatures equal to or higher than 130 °C at which the sheath component is melted, but lower than 230 °C at which the core component PET is melted.

A nonwoven fabric is preferable as the material for forming the topsheet 2 as mentioned above. As the materials for forming the backsheet 3, the absorbent core 4, the sheet material 61 for forming an upstanding gather, the elastic members 62, 64, 81 and the fastening tape 5, those, which are normally used for a disposable diaper, can be used without any particular limitation. For example, as the sheet material 61 for forming an upstanding gather, there can be used a spunbond, a spunbond/meltblown/ spunbond, a spunbond/meltblown/meltblown/spunbond, an airtrough nonwoven fabric and the like. Particularly preferably, they have hydrophobic properties.

A disposable diaper according to another embodiment of the present invention will be described next. FIGS. 6 and 7 are illustrations, which correspond to FIG. 3, each showing a sectional view in the widthwise direction of a disposable diaper according to another embodiment of the present invention. Those points of the disposable diapers shown in FIGS. 6 and 7, which are not particularly described, are the same as the above-mentioned disposable diaper 1 and the description on the above-mentioned disposable diaper 1 is applicable thereto, where appropriate.

In a disposable diaper 1A shown in FIG. 6, a hydrophobic sheet material 31 is adhesively laminated on that section of the sheet material 30 for forming a backsheet which covers a skin non-contacting side of an absorbent core 4, which extends outward in the widthwise direction from each side edge 4c of the absorbent core 4, and opposite side portions 3a of a backsheet 3 is composed of those sheet materials 30, 31, thereby exhibiting a dual layer structure. An outward extended topsheet 2a from a basal end 63 of an upstanding gather 6 is joined to the opposite side portions 3a exhibiting a dual structure in the backsheet 3. An outward extended backsheet 2a from the basal end 63 of the upstanding gather 6 is formed with a liquid shut-off regions 21C' which is similar

to the liquid shut-off region 21C of the disposable diaper 1. In this disposable diaper 1A, the sealing between the top and bottom surfaces at the opposite side portions of the diaper is achieved by an adhesive agent for joining the sheet material 61 for forming an upstanding gather and the topsheet 2 together, the liquid shut-off region 21C' formed on the topsheet 2, and an adhesive agent 7b for joining the topsheet 2 and the backsheet 3 together. The upstanding gather 6 in this disposable diaper 1A includes only a single elastic member 62. In FIG. 6, reference numeral 8 denotes an elastic member for forming a leg gather.

A disposable diaper 1B shown in FIG. 7 is different from the disposable diaper 1A only in the respect that the former includes, instead of the hydrophobic sheet material 31 in the disposable diaper 1A of FIG. 6, a hydrophilic sheet material 32 having a liquid shut-off region 33 which is similar to the liquid shut-off region 21C'. The opposite side portions 3a of the backsheet 3 in this disposable diaper 1B comprises a sheet material 30 extending outward in the widthwise direction beyond opposite side edges 4c of the absorbent core 4 and the sheet material 32 adhesively laminated on the sheet material 30. According to the disposable diapers 1A, 1B shown in FIGS. 6 and 7, there can be exhibited the similar effect to that of the disposable diaper 1.

The present invention should not be limited to the above embodiments. For example, although a method for forming the liquid shut-off region on the topsheet is preferably a heat-seal, it may be an ultrasonic seal. Or otherwise, the liquid shut-off region may be formed on the topsheet by sufficiently impregnating a thermoplastic resin, a wax, a hot-melt, a foamed body having a closed cell, a resin plasticized by water, a water-absorptive polymer or the like into fiber voids of the nonwoven fabric. Among them, the hot-melt is preferable and particularly preferably a hot-melt having less tackiness (in blending of the hot-melt, the molecular weight of the base resin is high and the blending ratio is high). The coating quantity of the hot-melt is preferably 20 to 100 g/m², and the coating system is preferably in the form of a plane or a bead using a coater. The kinds of usable hot-melt are not particularly limited. A styrene-based hot-melt, an olefin-based hot-melt, a solvent, a viscous agent, an aqueous tacky agent, or the like can be used.

In the above embodiments, although upstanding gathers are not formed on the opposite end portions in the longitudinal direction of the diaper, upstanding gathers may be formed on the both or one end portion in the longitudinal direction in the absorbent article of the present invention. It is also accepted that no upstanding gathers are formed on the opposite side portions in the longitudinal direction of the absorbent article and upstanding gathers are formed only on the both or one end portion. The liquid shut-off regions may be formed only on the peripheral edge portion of the absorbent core in the both side portions or both or one end portion in the longitudinal direction of the absorbent article. The liquid shut-off regions on the topsheet 2 may be joined to other sheets than the sheet for forming an upstanding gather. In the method for manufacturing an absorbent article, the location where the liquid shut-out portions are arranged, is not particularly limited. In the obtained absorbent article, the oozing of a body liquid in the topsheet can be prevented at various locations and the anti-leak effect can be enhanced in various manners. For example, in addition to the arrangement of the liquid shut-off regions located at an area outside the periphery of the absorbent core, sealed portions similar to the liquid shut-off regions may be arranged in a lattice shape over the entire surface of the skin contacting surface of the absorbent core. Aside from the shorts type disposable diaper, the present invention can likewise be applied to a pad of an incontinent person and a sanitary napkin.

[Example 1]

(1) Formation of Topsheet w/Liquid Shut-off region

A liquid shut-off region having a width of 5 mm was linearly formed on the under-mentioned nonwoven fabric by heat seal [seal temperature (set temperature, the same shall apply hereinafter): 160 °C] and a topsheet 2A was obtained.

Constitution of Nonwoven Fabric

Fiber Composition: fiber of a core-sheath structure whose core is
polyethylene-terephthalate (PET, m.p. 230°C)
and whose sheath is polyethylene (PE, m.p. 135°C)

Fiber Diameter: 2.7 (DTEX) Basis Weight: 30 g/m²

Method of Manufacture: Airthrough

(2) Making of Diaper

An absorbent core having a high absorption polymer dispersed in pulp fibers was placed on a backsheet whose central portion is twisted, and the obtained topsheet 2A is arranged on the absorbent core such that its liquid shut-off region is located outside the
5 absorbent core at an end portion on the stomach side of the diaper. Thereafter, a hydrophobic sheet having an elastic member was fixed to the end portion on the stomach side such that its basal end is located on the end portion of the absorbent core, and a prescribed leg portion elastic member was arranged on each of the opposite left and right side portions in the longitudinal direction of the diaper. By doing so, a diaper
10 was obtained.

[Example 2]

A diaper was manufactured in the same manner as the embodiment 1 except that a liquid shut-off region was formed by changing (or resetting) the seal temperature for the heat seal to 180 °C. When the seal temperature was changed to 140 °C, the liquid
15 shut-off region could not be formed. When the seal temperature was changed to 200 °C, the base material strength (adequate processing suitability) was lowered and therefore, no diaper was manufactured.

[Example 3]

A diaper was manufactured in the same manner as the embodiment 1 except that the
20 nonwoven fabric is change to another nonwoven fabric having the under-mentioned constitution and the seal temperature was changed to 140°C.

Constitution of Nonwoven Fabric: nonwoven fabric of a dual structure

Upper Layer: fiber-based 3.3 (DTEX), fiber length 51 (mm)

basis weight 15 (g/m²)

25 Lower Layer: fiber-based 5.5 (DTEX), fiber length 51 (mm)

basis weight 15 (g/m²)

Fiber Composition of Upper and Lower Layers:

fiber of a core-sheath structure whose core is

polypropylene (PP. m.p. 160°C)

30 and whose sheath is polyethylene (PE, m.p. 130°C)

Method of Manufacture: Airthrough

[Example 4]

A diaper was manufactured in the same manner as the embodiment 3 except that a liquid shut-off region was formed by changing the seal temperature for the heat seal to
5 160 °C. When the seal temperature was changed to 120 °C, the liquid shut-off region could not be formed. When the seal temperature was changed to 180 °C, the base material strength (adequate processing suitability) was lowered and therefore, no diaper was manufactured.

[Comparative Example 1]

10 A diaper was manufactured in the same manner as the embodiment 1 except that the nonwoven fabric of the embodiment 1 was used without being subjected to heat sealing.

[Performance Evaluation: Easy leak from the stomach side]

Easy leak from the stomach side was evaluated in the under-mentioned manner with respect to the diapers obtained in the embodiments and in the comparative embodiment.
15 That is to say, thirty pieces of the obtained diapers were distributed to each of 10 monitors and the number of the diapers in which the leak occurred from the stomach side, was counted. The number of the diapers in which the leak occurred from the stomach side (stomach-side leak number) was set to the total number which the ten monitors handled or used. The result is shown in Table 1.

20 Table 1 shows the heat seal temperature together with the results of evaluation, which was carried out in the under-mentioned manner, with respect to the restraining effect of oozing in the topsheet (the effect for preventing the migration of a body liquid through the interior of the topsheet) and the base material strength (adequate processing suitability).

25 [Restraining Effect of Oozing]

A sheet material for forming an upstanding gather, a topsheet and a backsheet were composited in this order through an adhesive agent (5 g/m²) and placed on an

inclination plate of 10 degrees. A colored water of 10 ml was dropped on the topsheet and it was observed how the liquid penetrates through the interior of the topsheet. When the oozing was stopped at the liquid shut-off region, it was indicated by ⊙, when there was observed some traces of oozing at the seal portion but no liquid was leaked outside, it was by ⊙, and when the liquid oozing was not stopped, it was indicated by ×.

[Base Material Strength (Adequate Processing Suitability)]

A nonwoven fabric was cut having 100 mm in the longitudinal direction and 50 mm in width and subjected to a tensile test under the condition of 300 mm/min in rate of pulling using a Tensilon tensile test machine. Those having 30N or more on average of five pieces (or sheets) were indicated by ○.

Table 1

	Heat-seal temperature (°C)	Restraining effect of oozing	Base material strength (Adequate processing suitability)	Leak occurred from the stomach side (Number)
Example 1	160	○	○	4
Example 2	180	⊙	○	3
Example 3	140	○	○	3
Example 4	160	⊙	○	4
Comparative Example 1	-	×	○	9

It will be appreciated, as apparent from Table 1, that the disposable diapers (invented articles) of the respective embodiments, when compared with those of the comparative embodiment, are extensively reduced in number of the diapers in which the leak occurred from the stomach side and are excellent in anti-leak performance.

INDUSTRIAL APPLICABILITY

The absorbent article of the present invention is excellent in workability and anti-leak property, capable of exhibiting a sufficient anti-leak effect even in the case where a bulky topsheet is used, good in productivity and capable of being manufactured at a low cost. In particular, excellent anti-leak property can be exhibited only by processing the


topsheet without using plural sheets, so that the absorbent article of the present invention can be manufactured efficiently and at a low cost.

CLAIMS

1. An absorbent article including a liquid-permeable topsheet, a liquid-impermeable backsheet and a liquid-retentive absorbent core interposed between said topsheet and said backsheet, said absorbent article being substantially vertically elongated and having
5 an upstanding gather,
wherein said topsheet has a liquid shut-off region in a linear shape which prevents liquid migration within said topsheet, and said liquid shut-off region is located at an area outside the periphery of said absorbent core and is formed independent of a joined section between said topsheet and a sheet material for forming said upstanding gather.
- 10 2. The absorbent article according to claim 1, wherein said topsheet extends outward beyond a basal end of said upstanding gather, at least a part of the extended section of said topsheet is joined to said backsheet, and said liquid shut-off region is located on the extended section of said topsheet.
- 15 3. The absorbent article according to claim 1, wherein said topsheet comprises a thermally fusible material, and said liquid shut-off region is formed by melting said thermally fusible material.
4. The absorbent article according to claim 3, wherein said topsheet is not thermally bonded to other sheet materials at said liquid shut-off region.
- 20 5. The absorbent article according to claim 4, wherein said liquid shut-off region is located over the widthwise direction of said absorbent article at both or one of the longitudinal end portions of said absorbent article.
- 25 6. The absorbent article according to claim 1, wherein said article does not have said upstanding gather at both or one of the longitudinal end portions of said article, and said liquid shut-off region is located over the widthwise direction of said article at the longitudinal end portion(s) where said upstanding gather is not located.

7. A method for manufacturing an absorbent article including a liquid permeable topsheet, a liquid impermeable backsheet and a liquid-retentive absorbent core interposed between said topsheet and said backsheet, said topsheet having a liquid shut-off region in a linear shape for preventing liquid migration within said topsheet,
- 5 said method comprising preliminarily forming said liquid shut-off region at said topsheet and then arranging said topsheet at a predetermined location of said absorbent article.

Fig. 1



2/3

Fig. 2




Fig. 3




Fig. 4




Fig. 5(a)




Fig. 5(b)




Fig. 6





Fig. 7



INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP 00/07754

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61F13/494

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 743 246 A (LAWSON MICHAEL I) 10 May 1988 (1988-05-10) column 4, line 6 - line 35; figures	1-7
Y	EP 0 264 238 A (PROCTER & GAMBLE) 20 April 1988 (1988-04-20) column 5, line 27 - line 45; figures	1-7
Y	US 4 015 604 A (CSILLAG CHARLES) 5 April 1977 (1977-04-05) claims; figures	4
A	US 4 200 103 A (BLACK ADAM R ET AL) 29 April 1980 (1980-04-29) claims; figures	1, 3, 4, 6, 7
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

31 January 2001

Date of mailing of the international search report

13/02/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Douskas, K

INTERNATIONAL SEARCH REPORT

Int: .ional Application No

PCT/JP 00/07754

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 762 642 A (COLES PETER ET AL) 9 June 1998 (1998-06-09) claims; figures	1,4
A	US H1746 H (MARSHALL III ROBERT E LEE ET AL) 4 August 1998 (1998-08-04) claims; figures	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int: Jonal Application No

PCT/JP 00/07754

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4743246 A	10-05-1988	US 4695278 A	22-09-1987
		AT 54048 T	15-07-1990
		AU 579080 B	10-11-1988
		AU 6369186 A	16-04-1987
		CA 1311879 A	29-12-1992
		DE 3672195 D	02-08-1990
		DK 481986 A	12-04-1987
		EG 17945 A	30-03-1991
		EP 0219326 A	22-04-1987
		FI 864098 A,B,	12-04-1987
		GB 2181336 A,B	23-04-1987
		GR 3000768 T	10-10-1991
		HK 53592 A	30-07-1992
		IE 59004 B	15-12-1993
		JP 6093901 B	24-11-1994
		JP 62250201 A	31-10-1987
		KR 9408959 B	28-09-1994
		MX 161320 A	10-09-1990
		NZ 217887 A	26-07-1995
		PH 23270 A	23-06-1989
		PT 83496 A,B	01-11-1986
		SG 52392 G	24-07-1992
EP 0264238 A	20-04-1988	US 4738677 A	19-04-1988
		AT 67656 T	15-10-1991
		AU 613879 B	15-08-1991
		AU 7950387 A	14-04-1988
		BR 8705462 A	24-05-1988
		CA 1334319 A	14-02-1995
		DE 3773323 A	31-10-1991
		DK 530487 A	11-04-1988
		EG 18192 A	30-08-1992
		ES 2024519 T	01-04-2000
		FI 874458 A,B,	11-04-1988
		GR 3032645 T	30-06-2000
		GR 3002791 T	25-01-1993
		HK 47094 A	20-05-1994
		IE 60690 B	10-08-1994
		JP 2517622 B	24-07-1996
		JP 63182402 A	27-07-1988
		KR 9609237 B	16-07-1996
		MX 170748 B	13-09-1993
		NZ 222114 A	26-07-1995
		NZ 238532 A	26-07-1995
		NZ 247474 A	26-07-1995
		PT 85889 A,B	01-11-1987
		TR 23295 A	14-09-1989
		US 4816025 A	28-03-1989
		US 4938755 A	03-07-1990
US 4015604 A	05-04-1977	AR 216758 A	31-01-1980
		AT 970076 A	15-05-1981
		AU 504756 B	25-10-1979
		AU 2155277 A	27-07-1978
		BE 850009 A	30-06-1977
		BR 7701456 A	08-11-1977
		DE 2658606 A	06-10-1977
		ES 236462 Y	16-11-1978

INTERNATIONAL SEARCH REPORT

Information on patent family members.

International Application No

PCT/JP 00/07754

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4015604 A		FR 2355513 A	20-01-1978
		GR 60785 A	28-08-1978
		IN 145028 A	12-08-1978
		IT 1073165 B	13-04-1985
		JP 1263674 C	16-05-1985
		JP 52118358 A	04-10-1977
		JP 59039134 B	21-09-1984
		LU 76767 A	30-06-1977
		NL 7700489 A	27-09-1977
		NZ 183124 A	11-01-1979
		PH 13089 A	23-11-1979
		PT 66051 A, B	01-02-1977
		ZA 7607658 A	30-08-1978
		ZM 1977 A	21-11-1977
US 4200103 A	29-04-1980	AR 215798 A	31-10-1979
		AU 525100 B	21-10-1982
		AU 4638279 A	01-11-1979
		BE 875942 A	29-10-1979
		BR 7902537 A	30-10-1979
		CA 1118955 A	02-03-1982
		DE 2917181 A	08-11-1979
		DK 175879 A	29-10-1979
		ES 250488 U	01-09-1980
		FI 791375 A	29-10-1979
		FR 2424021 A	23-11-1979
		GB 2019727 A, B	07-11-1979
		IE 48215 B	31-10-1984
		IN 148710 A	23-05-1981
		IT 1120415 B	26-03-1986
		JP 1485696 C	14-03-1989
		JP 54147695 A	19-11-1979
		JP 62000703 B	09-01-1987
		LU 81197 A	10-09-1979
		MX 150172 A	29-03-1984
		NL 7903305 A	30-10-1979
		NO 791422 A	30-10-1979
		NZ 190234 A	23-01-1981
		PH 16495 A	28-10-1983
		PT 69557 A	01-05-1979
		SE 7903681 A	29-10-1979
		ZA 7902041 A	26-11-1980
US 5762642 A	09-06-1998	EP 0626158 A	30-11-1994
		AU 695473 B	13-08-1998
		AU 6942094 A	20-12-1994
		CA 2163079 A	08-12-1994
		EP 0746296 A	11-12-1996
		JP 8510664 T	12-11-1996
		WO 9427538 A	08-12-1994
US H1746 H	04-08-1998	AU 6776394 A	20-12-1994
		AU 7314198 A	20-08-1998
		CA 2163194 A	08-12-1994
		EP 0699063 A	06-03-1996
		JP 8510665 T	12-11-1996
		NZ 266321 A	24-11-1997
		WO 9427539 A	08-12-1994